

# Pioneer XLE Series Engineered Water Tanks



Lakota Tank Company  
Residential, Commercial,  
and Agricultural

**Engineered permittable tanks for fire protection, drinking water, and other commercial applications.**

**Standard XLE Series tank kit includes:**

Commercial tank body, trusses and roof sheets, top hoop, bottom hoop and anchors, AQUALINER® Fresh, geotextile underlay, lockable roof access hatch and ladder, 2" outlet with ball valve, 6" overflow, sacrificial anodes, and standard engineering drawings. Pioneer Water Tanks America is not responsible for securing permits or special engineering.

Zincalume® Tanks	Diameter	Height	Nominal US Gallons	Effective Volume (Net Usable Gallons)**
XLE 10/2	17' 7"	7' 2"	12,946	11,201
XLE 13/2	19' 9"	7' 2"	16,392	14,132
XLE 15/2	22' 0"	7' 2"	20,243	17,535
XLE 23/2	26' 4"	7' 2"	29,093	25,124
XLE 30/2	30' 9"	7' 2"	39,626	34,257
XLE 40/2	35' 2"	7' 2"	51,785	44,806
XLE 50/2	39' 6"	7' 2"	65,567	56,528
XLE 50/3	39' 6"	10' 7"	97,148	87,848

Mangrove® Tanks	Diameter	Height	Nominal US Gallons	Effective Volume (Net Usable Gallons)**
XLE 23/2	26' 4"	7' 2"	29,093	25,124
XLE 50/2	39' 6"	7' 2"	65,567	56,528
XLE 50/3	39' 6"	10' 7"	97,148	87,848

XLE Series tanks must be installed by a Pioneer Water Tanks Authorized Installer.

XLE Series tanks are backed by a 20-year warranty when installed by a Pioneer Water Tanks Authorized Installer and site grading is third-party verified (permitted). Terms and conditions apply.

\*\*Net usable gallons for Fire Protection Tanks are based on 6" freeboard and 6" loss below the anti-vortex plate.

